## versatile<sup>TM</sup> 4C Mailbox, 4C07S-1P 17" R.O. 17 1/2" ACTUAL **DEPTH** 16 1/2" MAX R.O. 16 1/4" MIN 26 3/4" 26 1/8" MAX R.O. 25 7/8" MIN **ACTUAL** 39 3/4" (TO PARCEL LOCK) 27 1/8" FROM 28" FINISHED FLOOR (TO BOTTOM TO BOTTOM OF R.O. SHELF) FINISHED FLOOR

## Notes:

- 1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
  - a. At least one customer compartment shall be positioned less then 48" above finished floor (AFF).
  - b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
  - c. No patron (tenant) lock shall be positioned more than 67" AFF.
  - d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
  - e. The USPS Arrow lock shall be positioned 36"- 48" AFF.
- 2. This 4C mailbox can also be used for private applications.
- 3. The rough opening width for multi-unit 4C installations is provided using the Florence configurator: www.florencemailboxes.com/configurator.

## COMPARTMENT CHART

		DESCRIPTION	COMPARTMENT	COMPARTMENT SIZE	QTY.
		PARCEL	PL6	20-1/2" H x 12" W x 15" D	1
PRODUCT SERIES:	VERSATILETM 4C FRONT LOAD MAILBOX				

MODEL 4C07S-1P REV E
SCALE NONE LAST REV DATE 07/02/19
DRAWING NUMBER DRAWN BY
4C07S-1PCS RAK